



Automatic Level

NA Series Automatic Level

Features:

- Air-dampened, wire-hung compensator with X wire Design can work more reliable and more adaptable against vibrations and shocks.
- Fine motion knobs on left and right sides friction-braked rotation, endless horizontal drive.
- Penta prism for easy bubble viewing.
- Excellent sealed structure for using in any weather conditions.
- 5/8"x11 thread to fit standard tripod, suitable for both flat and dome head tripod.

Specifications:

Item no:	NA20	NA24	NA28	NA32
Magnification:	20X	24X	28X	32X
Standard deviation for 1km double run leveling	2.5mm	2.0mm	1.5mm	1.0mm
Objective aperture:	38mm	38mm	38mm	38mm
Field of view:	1°20'			
Shortest focus distance:	0.3m			
Compensator type:	wire-hung and air-damping			
Working range of compensator:	±15'			
Levelling accuracy:	±0.5"			
Circular vial:	8/2mm			
Horizontal circle:	360° or 400G for option			
Weight:	1.4KG			
Standard outfit:	automatic level, plumb bob, adjusting wrench, instruction manual, plastic carrying case.			



AL Series Automatic Level

Features:

- Improved structure of rack and gear system avoid dislocation.
- Reliable air-damping, wire-hung compensator with X wire design.
- Excellent sealed structure for using in any weather conditions.
- 5/8"x11 thread to fit standard tripod, suitable for both flat and dome head tripod.

Specifications:

Item no:	AL20	AL24	AL28	AL32
Magnification:	20X	24X	28X	32X
Standard deviation for 1km double run leveling	2.5mm	2.0mm	1.5mm	1.0mm
Objective aperture:	38mm	38mm	38mm	38mm
Field of view:	1°20'			
Shortest focus distance:	0.3m			
Compensator type:	wire-hung and magnetic-damping			
Working range of compensator:	±15'			
Levelling accuracy:	±0.5"			
Circular vial:	8/2mm			
Horizontal circle:	360° or 400G for option			
Weight:	1.4KG			
Standard outfit:	automatic level, plumb bob, adjusting wrench, instruction manual, plastic carrying case.			

